

Model:	VA-24040D006	Technologic Data
Certificate		CE
Based on:		IEC 61347
Input	Rated voltage:	AC170~250V
	Frequency:	50~60Hz
	Input power (Loading):	≤ 50W
Output	Output voltage (Loading):	DC 24V±0.5V
	Output current (loading):	DC 1.7A
	Short-circuits protect:	Output shorted 3 seconds, and will work normally after separated.
	Over loading:	Protection
Voltage resistance	Input-Output	AC 1.5KV/5mA 1Min
	Input-Housing	AC 1.5KV/5mA 1Min
Working Temperature		-25℃~+40℃

Feature testing

Testing Contents	Testing Qty	1	2	3	4	5
Input voltage:		AC 170V~250V 50Hz				
High voltage test	Input—Output:	OK	OK	OK	OK	OK
	Input— Housing:	OK	OK	OK	OK	OK
Input power (Loading current 1.7A)		48.5W	48.0W	48.0W	48.5W	48.0W
Output voltage (Loading current 1.7A)		24.4V	24.4V	24.0V	24.0V	23.8V
Output voltage (Loading current 0A)		24.0V	24.0V	24.0V	24.0V	24.1V
Short-circuit:		OK	OK	OK	OK	OK
Over loading:		OK	OK	OK	OK	OK
Verdict:		Pass				

